

PCSC's Fault Tolerant Technology is Pushing Access Control to the EDGE™



Powered by LINEX™ Fault Tolerant Architecture Patent Pending

Introducing the world's first Fault Tolerant Single Door Controller and reader combination. Utilizing PCSC's patent pending Fault Tolerant system design and HID Global's EDGE™ technology provides for an unparalleled solution.

- PoE (Power Over Ethernet)
- Global Anti-Passback
- 3 Levels of Anti-Passback
- Handicapped Access
- 365 Holidays
- Supervisory Access
- Escort Control
- FIPS Compliant
- Remote Managed
- Global Input/Output Control
- Pre-Door Ajar Alarm



PCSC
Next Generation Security Solutions Provider
www.pcsc.com

60

Circle 6 on card.

1109 | NEW PRODUCTS

Dome Camera PTZ



Bosch's AutoDome Easy II indoor PTZ camera features 360-degree continuous rotation, a 120x zoom autofocus lens and 12 privacy masks. The camera provides digital imaging technology with 530 TV lines of resolution and color imaging in low-light conditions. Built-in Billix technology provides two-way communication through the unit's video cable. The product is housed in heavy-duty tamper-resistant aluminum and a polycarbonate bubble. *Bosch Security Systems Inc.*

Circle 341 on card, or respond at www.secpdonline.com.

TV Lock Kit LCD and flat-screen protection



D&D Security's Flat-panel TV Security Kit is designed to protect LCD and plasma flat-screen TVs from theft. The product attaches to a TV's VESA holes. The kit features a 6-foot aircraft-strength security cable, a VESA screw pack, two VESA chassis fittings, a security plate and a heavy-duty padlock. A cap insert protects access to the TV's screw head. *D&D Security Resources.*

Circle 342 on card, or respond at www.secpdonline.com.

Biometric Access Control RFID



The ELECTRA smartI unit from TAB Systems provides multimodal biometric access control based on facial and voice recognition. The indoor unit mounts on the wall with an IP-65 compliant front panel and a 5.7-inch color touchscreen. The product is equipped with an RFID reader, PoE, a built-in camera, speakers, a microphone and internal memory. The unit's integrated communication ports and relay I/O controller controls lights, electronic locks, alarms and sensors. *TAB Systems Inc.*

Circle 343 on card, or respond at www.secpdonline.com.

Electric Strike Stainless-steel



Rutherford Controls' 0162 Electric Strike for rim exits is compatible with exit devices from most major manufacturers and is designed for any type of frame. The device features stainless-steel construction, dual voltage, plug-in wire connectors and 1/4-inch horizontal adjustment. The product is surface mounted and installs against a frame. *Rutherford Controls.*

Circle 344 on card, or respond at www.secpdonline.com.

Camera Head Industrial applications



R. Brooks' ICH-4 integrated camera head is designed for industrial applications. The PTZ camera weighs less than 10 lbs. and is constructed of cast aluminum. The unit features a 35-watt LED array package, a built-in laser, and 360-degree pan and tilt capabilities. The product is operational in 32 to 122 degrees Fahrenheit temperatures and equipped with an 18x optical and 12x digital zoom. *R. Brooks Associates Inc.*

Circle 345 on card, or respond at www.secpdonline.com.

Video Engine Thermal imaging



Cantronic Systems' VE1.6 thermal imaging video engine is designed for cooled thermal cameras. The device's digital board accepts camera link data at the input and analog/digital video at the output. The unit functions as a stand-alone or integrated engine with multiple detector and lens options. The engine features a 60 hertz frame rate, histogram equalization, digital zoom, autofocus, and network and RS-232 control. *Cantronic Systems.*

Circle 346 on card, or respond at www.secpdonline.com.